Contact: insidesales@talius.	<u>com</u> #	
Fax: 250.832.8577 Tel: 250.832.		
AG77	GUIDE RAILS: GR100	CUSTOMER NAME: Tag Name: Repeat Customer? Yes No Qty: Unit Location: Unit # Site Map# (if required)
3" (77 mm) 3/4" (19 mm) 3/4" (19 mm)		GUIDE RAILS PRE-DRILLING Pre-drill rails: 8.5 mm 10 mm 14 mm Thru Face
UNIT DIMENSIONS		SILLS
Does <u>your</u> B1 measurement inclu 2" (50 mm) upset to allow botto	m profile to clear Yes 🗆	☐ L-Shaped 22 x 42mm (7/8" x 1-11/16"), Cut at A2 Qty:
	Exit Hole Location Select Manual override exit location ght 1 (L2)	Check off on the diagram at the right where you want to have build-up, and then check off below, the build-up thickness required for each location Build up Tubing: Size: 2" x 1" 2" x 2" Location: Build up Tubing: Build up Tu
OPERATOR COMPONENT OPTIONS □ Standard Limit Motor Switch Style: □ Maintained □ Momentary □ Paddle Switch: □ SPDT □ DPDT □ Medium Security Key Switch Cover Plate: □ None □ Single □ Plastic □ Double □ Triple □ Decoflex 1 White		White
		ANTI-GRAFFITI COATING: Indicate which side on diagram below
Stainless Quadruple High Security Key Swite Surface Recess Keyed: Different Number of Keys Required:	Decoflex 5 White Somfy Keychain	Regular Reverse Bottom Guide Panel Rails Box Sill Build-up GARAGE PACKAGE: Includes RC200 and Contact Sensing Beams
Upgrade to Manual Overr	ide Motor (Select crank rod) vable w/Bell Removable with Univers.	
Somfy® Specialty Transmit ☐ Somfy MyLink™ ☐ Sr		NOTES

☐ RTS Digital Keypad ☐ Smoove® Faceplate Colour:_